

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **125**

Water absorption
capacity L/KG*: **0**

Net weight: **8**

Qty / pallet: **12**

ARTICLE CODE

BC1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 16 Cushions 40X40CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **156**

Water absorption capacity L/KG*: **0**

Net weight: **10**

Qty / pallet: **12**

ARTICLE CODE

BC2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4 Cushions 60X80CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BP101

 Oil absorption
 capacity L/KG*: **139**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **7.2**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP101-H

Oil absorption
capacity L/KG*: **130**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BP102

 Oil absorption
 capacity L/KG*: **139**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **7.2**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP102-H

Oil absorption
capacity L/KG*: **130**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BP103

Oil absorption capacity L/KG*:	63
Water absorption capacity L/KG*:	0
Net weight:	3.24
Qty / pallet:	40

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 30X30CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BP111-D

 Oil absorption
 capacity L/KG*: **120**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **7.68**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BP201

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **108**

Water absorption
capacity L/KG*: **0**

Net weight: **6**

Qty / pallet: **20**

ARTICLE CODE

BP201A

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP201-H

Oil absorption capacity L/KG*: **87**Water absorption capacity L/KG*: **0**Net weight: **6**Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **108**

Water absorption capacity L/KG*: **0**

Net weight: **6**

Qty / pallet: **20**

ARTICLE CODE

BP202

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2X50 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP202-H

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **0**

Net weight: **6**

Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2X50 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BP203

Oil absorption capacity L/KG*: **49**Water absorption capacity L/KG*: **0**Net weight: **2.7**Qty / pallet: **48**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 30X30CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **49**

Water absorption
capacity L/KG*: **0**

Net weight: **2.7**

Qty / pallet: **48**

ARTICLE CODE

BP203-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BP211-D

Oil absorption capacity L/KG*:	90
Water absorption capacity L/KG*:	0
Net weight:	6.24
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP211-H

Oil absorption capacity L/KG*:	85
Water absorption capacity L/KG*:	0
Net weight:	6.4
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP213-H

Oil absorption capacity L/KG*:	39
Water absorption capacity L/KG*:	0
Net weight:	2.88
Qty / pallet:	48

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT:	No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
SECURITY:	No specific risk. For further information, please refer to the material safety data sheet.
STORAGE:	Store in a dry and cool place.
DISPOSABILITY:	The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BP218-D

Oil absorption capacity L/KG*:	72
Water absorption capacity L/KG*:	0
Net weight:	4.992
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8X10 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP218-H

Oil absorption capacity L/KG*: **68**
 Water absorption capacity L/KG*: **0**
 Net weight: **5.12**
 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8X10 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BP221-D

Oil absorption capacity L/KG*:	88
Water absorption capacity L/KG*:	0
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP221-H

Oil absorption capacity L/KG*:	80
Water absorption capacity L/KG*:	0
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BP223-H

Oil absorption capacity L/KG*:	36
Water absorption capacity L/KG*:	0
Net weight:	2.988
Qty / pallet:	48

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **0**

Net weight: **4.8**

Qty / pallet: **20**

ARTICLE CODE

BP300XX401C11

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10X10 Pads 40X40CM

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **166**

Water absorption
capacity L/KG*: **0**

Net weight: **8.64**

Qty / pallet: **15**

ARTICLE CODE

BR101

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR101-H

Oil absorption capacity L/KG*:	156
Water absorption capacity L/KG*:	0
Net weight:	8.64
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BR102

 Oil absorption
 capacity L/KG*: **166**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8.64**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR102-D

Oil absorption capacity L/KG*:	115
Water absorption capacity L/KG*:	0
Net weight:	8.64
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR102-H

Oil absorption capacity L/KG*:	156
Water absorption capacity L/KG*:	0
Net weight:	8.64
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR111-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	0
Net weight:	9.216
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR112-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	0
Net weight:	9.216
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

BR201

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR201-D

 Oil absorption
 capacity L/KG*: **173**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **9.6**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR201-H

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BR202

 Oil absorption
 capacity L/KG*: **173**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **9.6**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR202-H

Oil absorption capacity L/KG*: **139**

Water absorption capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR211-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	0
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR211-H

Oil absorption capacity L/KG*:	136
Water absorption capacity L/KG*:	0
Net weight:	10.24
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR212-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	0
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.



TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR212-H

Oil absorption
capacity L/KG*: **136**

Water absorption
capacity L/KG*: **0**

Net weight: **10.24**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR221/100-D

Oil absorption capacity L/KG*:	176
Water absorption capacity L/KG*:	0
Net weight:	13.28
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 1X40M length perforated 50 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT:	No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
SECURITY:	No specific risk. For further information, please refer to the material safety data sheet.
STORAGE:	Store in a dry and cool place.
DISPOSABILITY:	The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR221-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT:	No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
SECURITY:	No specific risk. For further information, please refer to the material safety data sheet.
STORAGE:	Store in a dry and cool place.
DISPOSABILITY:	The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR221-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BR222-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.



TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

BR222-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT:	No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
SECURITY:	No specific risk. For further information, please refer to the material safety data sheet.
STORAGE:	Store in a dry and cool place.
DISPOSABILITY:	The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

BR300XX845BS1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BS1

 Oil absorption
 capacity L/KG*: **125**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Socks 7.5CMX1.2M

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	To absorb and clean small quantity
SOCKS	Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

BS2

 Oil absorption
 capacity L/KG*: **125**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8 Socks 7.5CMX3M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SOCKS

Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

BS3


 Oil absorption
 capacity L/KG*: **94**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Sock 7.5CMX18M

APPLICATION

BLUE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	To absorb and clean small quantity
SOCKS	Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **297**

Water absorption
capacity L/KG*: **171**

Net weight: **19**

Qty / pallet: **6**

ARTICLE CODE

CB25

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø20CMX5M

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



To absorb and clean small quantity

FLOCKS BOOMS

Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain

PURE FIBRE

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CC1

Oil absorption capacity L/KG*: **125**Water absorption capacity L/KG*: **72**Net weight: **8**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 16 Cushions 40X40CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CC2

 Oil absorption
 capacity L/KG*: **156**

 Water absorption
 capacity L/KG*: **90**

 Net weight: **10**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4 Cushions 60X80CM

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



To absorb and clean small quantity

CUSHIONS INDUSTRY

Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CC25

Oil absorption capacity L/KG*: **63**Water absorption capacity L/KG*: **36**Net weight: **4.1**Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 32 Cushions 20X25CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CC501

Oil absorption capacity L/KG*:	40
Water absorption capacity L/KG*:	24
Net weight:	2.28
Qty / pallet:	42

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Pads 30X40CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
ULTRA HEAVY WEIGHT	Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CC501-S

Oil absorption capacity L/KG*:	40
Water absorption capacity L/KG*:	24
Net weight:	2.28
Qty / pallet:	42

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Pads 30X40CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
ULTRA HEAVY WEIGHT	Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CC502

Oil absorption capacity L/KG*: **67**Water absorption capacity L/KG*: **40**Net weight: **3.8**Qty / pallet: **30**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 10 Pads 50X80CM

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CCE1

Oil absorption capacity L/KG*: **125**Water absorption capacity L/KG*: **72**Net weight: **8**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 16 Cushions 40X40CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

CP101

 Oil absorption
 capacity L/KG*: **139**

 Water absorption
 capacity L/KG*: **72**

 Net weight: **7.2**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

CP101-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

CP101-D

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CP101-H

Oil absorption
capacity L/KG*: **130**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

CP101-S

 Oil absorption
 capacity L/KG*: **139**

 Water absorption
 capacity L/KG*: **72**

 Net weight: **7.2**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

CP102

 Oil absorption
 capacity L/KG*: **139**

 Water absorption
 capacity L/KG*: **72**

 Net weight: **7.2**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CP102-H

Oil absorption
capacity L/KG*: **130**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

CP103

Oil absorption capacity L/KG*:	63
Water absorption capacity L/KG*:	33
Net weight:	3.584
Qty / pallet:	40

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 28X32CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP111-D

 Oil absorption
 capacity L/KG*: **120**

 Water absorption
 capacity L/KG*: **70**

 Net weight: **7.68**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP201

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **60**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP201-B

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **60**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CP201-H

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **60**

Net weight: **6**

Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP202

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **60**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2X50 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP203

Oil absorption capacity L/KG*: **49**Water absorption capacity L/KG*: **27**Net weight: **2.7**Qty / pallet: **48**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP203-B

Oil absorption capacity L/KG*: **49**Water absorption capacity L/KG*: **27**Net weight: **2.7**Qty / pallet: **48**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP203-S

Oil absorption capacity L/KG*: **49**Water absorption capacity L/KG*: **27**Net weight: **2.7**Qty / pallet: **48**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 30X30CM

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP211-D



Oil absorption capacity L/KG*:	90
Water absorption capacity L/KG*:	50
Net weight:	6.24
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CP211-H

Oil absorption capacity L/KG*:	85
Water absorption capacity L/KG*:	58
Net weight:	6.4
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



Products are reinforced on one side to give the product durability.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CP221-D



Oil absorption capacity L/KG*:	88
Water absorption capacity L/KG*:	60
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CP221-H

Oil absorption capacity L/KG*:	80
Water absorption capacity L/KG*:	60
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CPA4163H

Oil absorption capacity L/KG*:	80
Water absorption capacity L/KG*:	60
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **166**

Water absorption
capacity L/KG*: **87**

Net weight: **8.64**

Qty / pallet: **15**

ARTICLE CODE

CR101

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR101-H

Oil absorption
capacity L/KG*: **156**

Water absorption
capacity L/KG*: **87**

Net weight: **8.64**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **166**

Water absorption
capacity L/KG*: **87**

Net weight: **8.64**

Qty / pallet: **15**

ARTICLE CODE

CR101-S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	166
Water absorption capacity L/KG*:	87
Net weight:	8.64
Qty / pallet:	15

ARTICLE CODE

CR102

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	83
Water absorption capacity L/KG*:	44
Net weight:	4.32
Qty / pallet:	24

ARTICLE CODE

CR102/2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X60M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	83
Water absorption capacity L/KG*:	44
Net weight:	4.32
Qty / pallet:	24

ARTICLE CODE

CR102-1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X60M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

CR102-B

 Oil absorption
 capacity L/KG*: **111**

 Water absorption
 capacity L/KG*: **58**

 Net weight: **5.76**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR102-H

Oil absorption capacity L/KG*:	156
Water absorption capacity L/KG*:	87
Net weight:	8.64
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **166**

Water absorption
capacity L/KG*: **87**

Net weight: **8.64**

Qty / pallet: **15**

ARTICLE CODE

CR102-S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

CR201

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

CR201-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR201-H

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

CR202

 Oil absorption
 capacity L/KG*: **173**

 Water absorption
 capacity L/KG*: **96**

 Net weight: **9.6**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **48**

Net weight: **4.8**

Qty / pallet: **24**

ARTICLE CODE

CR202/2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR202-H

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CR211-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	80
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR211-H

Oil absorption
capacity L/KG*: **136**

Water absorption
capacity L/KG*: **93**

Net weight: **10.24**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



Products are reinforced on one side to give the product durability.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CR212-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	80
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR212-H

Oil absorption
capacity L/KG*: **136**

Water absorption
capacity L/KG*: **93**

Net weight: **10.24**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR212-H1

Oil absorption capacity L/KG*:	68
Water absorption capacity L/KG*:	47
Net weight:	5.12
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CR221-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR221-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CR222-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

CR222-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CR224-D

Oil absorption capacity L/KG*:	27
Water absorption capacity L/KG*:	18
Net weight:	1.992
Qty / pallet:	56

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
FOLDED ROLLS	To be use as a roll, a sock, a pad according to the spill.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	199
Water absorption capacity L/KG*:	120
Net weight:	11.4
Qty / pallet:	9

ARTICLE CODE

CR501

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X15M

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
ULTRA HEAVY WEIGHT	Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	199
Water absorption capacity L/KG*:	120
Net weight:	11.4
Qty / pallet:	9

ARTICLE CODE

CR502

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X15M

APPLICATION

YELLOW HYDROPHILIC	Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
ULTRA HEAVY WEIGHT	Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CS1

Oil absorption capacity L/KG*: **125**Water absorption capacity L/KG*: **72**Net weight: **8**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Socks 7.5CMX1.20M

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



To absorb and clean small quantity

SOCKS

Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

CS2

Oil absorption capacity L/KG*: **125**Water absorption capacity L/KG*: **72**Net weight: **8**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8 Socks 7.5CMX3M

APPLICATION

YELLOW HYDROPHILIC

Absorbs a wide spectrum of products (acids, alkaline solutions, acetate, chlorinated solvents, benzene, toluene, water, oil, etc...).



To absorb and clean small quantity

SOCKS

Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.

PURE FIBRE

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **254**

Water absorption
capacity L/KG*: **147**

Net weight: **16.28**

Qty / pallet: **12**

ARTICLE CODE

GB13

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø13CMX3M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	To absorb and clean small quantity
FLOCKS BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **125**

Water absorption
capacity L/KG*: **72**

Net weight: **8**

Qty / pallet: **12**

ARTICLE CODE

GC1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 16 Cushions 40X40CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **156**

Water absorption
capacity L/KG*: **90**

Net weight: **10**

Qty / pallet: **12**

ARTICLE CODE

GC2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4 Cushions 60X80CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **125**

Water absorption
capacity L/KG*: **72**

Net weight: **8**

Qty / pallet: **12**

ARTICLE CODE

GCE1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 16 Cushions 40X40CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	To absorb and clean small quantity
CUSHIONS INDUSTRY	Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GDT2534-D

Oil absorption capacity L/KG*:	11
Water absorption capacity L/KG*:	6
Net weight:	0.71
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.34CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GDT25-D

Oil absorption capacity L/KG*:	28
Water absorption capacity L/KG*:	16
Net weight:	1.92
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.56CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GDT25-D-S

Oil absorption capacity L/KG*:	28
Water absorption capacity L/KG*:	16
Net weight:	1.92
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.56CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GDT25-H

Oil absorption capacity L/KG*:	28
Water absorption capacity L/KG*:	16
Net weight:	1.92
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.56CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GDTM25-D

Oil absorption capacity L/KG*:	26
Water absorption capacity L/KG*:	20
Net weight:	2.85
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.56CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GM101-D

 Oil absorption
 capacity L/KG*: **96**

 Water absorption
 capacity L/KG*: **58**

 Net weight: **7.2**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X40M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottomlayer that acts as a barrier protecting the surface its used on making them ideal for use in areas where constant drips or overspray would otherwise contaminate the surface.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GM101-H

Oil absorption
capacity L/KG*: **96**

Water absorption
capacity L/KG*: **58**

Net weight: **7.2**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X40M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer that acts as a barrier protecting the surface its used on making them ideal for use in areas where constant drips or overspray would otherwise contaminate the surface.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GM107-D

Oil absorption capacity L/KG*:	32
Water absorption capacity L/KG*:	19
Net weight:	2.3625
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 0.70X15M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottomlayer that acts as a barrier protecting the surface its used on making them ideal for use in areas where constant drips or overspray would otherwise contaminate the surface.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GM109-D

Oil absorption capacity L/KG*:	41
Water absorption capacity L/KG*:	25
Net weight:	3.0375
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 0.90X15M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottomlayer that acts as a barrier protecting the surface its used on making them ideal for use in areas where constant drips or overspray would otherwise contaminate the surface.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE


GM310-D

Oil absorption capacity L/KG*:	42
Water absorption capacity L/KG*:	33
Net weight:	4.63
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 50 Mats 40X50CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM310-H

Oil absorption capacity L/KG*:	42
Water absorption capacity L/KG*:	33
Net weight:	4.63
Qty / pallet:	32

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 50 Mats 40X50CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM310-H100

Oil absorption capacity L/KG*:	84
Water absorption capacity L/KG*:	65
Net weight:	9.26
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Mats 40X50CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM310-H-S

Oil absorption capacity L/KG*:	42
Water absorption capacity L/KG*:	33
Net weight:	4.63
Qty / pallet:	32

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 50 Mats 40X50CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


GM311-D

Oil absorption capacity L/KG*:	100
Water absorption capacity L/KG*:	78
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Mats 0.40X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM311-H

Oil absorption capacity L/KG*:	100
Water absorption capacity L/KG*:	78
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Mats 0.40X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM311-H1

Oil absorption capacity L/KG*:	51
Water absorption capacity L/KG*:	39
Net weight:	5.556
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.40X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


GM312-D

Oil absorption capacity L/KG*:	100
Water absorption capacity L/KG*:	78
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT:	No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
SECURITY:	No specific risk. For further information, please refer to the material safety data sheet.
STORAGE:	Store in a dry and cool place.
DISPOSABILITY:	The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM312-H

Oil absorption capacity L/KG*:	100
Water absorption capacity L/KG*:	78
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM312-H-S

Oil absorption capacity L/KG*:	100
Water absorption capacity L/KG*:	78
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


GM313-D

Oil absorption capacity L/KG*:	150
Water absorption capacity L/KG*:	117
Net weight:	16.668
Qty / pallet:	8

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.20X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM313-H

Oil absorption capacity L/KG*:	150
Water absorption capacity L/KG*:	117
Net weight:	16.668
Qty / pallet:	8

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.20X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


GM314-D

Oil absorption capacity L/KG*:	200
Water absorption capacity L/KG*:	156
Net weight:	22.224
Qty / pallet:	6

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.60X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM314-H

Oil absorption capacity L/KG*:	200
Water absorption capacity L/KG*:	156
Net weight:	22.224
Qty / pallet:	6

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.60X30M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM314-H25

Oil absorption capacity L/KG*:	167
Water absorption capacity L/KG*:	130
Net weight:	18.52
Qty / pallet:	6

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.60X25M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


GM316-D

Oil absorption capacity L/KG*:	41
Water absorption capacity L/KG*:	32
Net weight:	4.4448
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Mats 60X80CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM316-H

Oil absorption capacity L/KG*:	41
Water absorption capacity L/KG*:	32
Net weight:	4.4448
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Mats 60X80CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


GM319-H

Oil absorption capacity L/KG*:	67
Water absorption capacity L/KG*:	52
Net weight:	7.408
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10 Mats 80X200CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GP101

 Oil absorption
 capacity L/KG*: **139**

 Water absorption
 capacity L/KG*: **72**

 Net weight: **7.2**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC

Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

GP101-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GP101-H

 Oil absorption
 capacity L/KG*: **130**

 Water absorption
 capacity L/KG*: **72**

 Net weight: **7.2**

 Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

GP101-S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

GP102

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GP102-H

Oil absorption
capacity L/KG*: **130**

Water absorption
capacity L/KG*: **72**

Net weight: **7.2**

Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	63
Water absorption capacity L/KG*:	33
Net weight:	3.24
Qty / pallet:	40

ARTICLE CODE

GP103

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 30X30CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GP111-D

Oil absorption capacity L/KG*: **120**Water absorption capacity L/KG*: **70**Net weight: **7.68**Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **108**

Water absorption
capacity L/KG*: **60**

Net weight: **6**

Qty / pallet: **20**

ARTICLE CODE

GP201

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GP201-H

 Oil absorption
 capacity L/KG*: **87**

 Water absorption
 capacity L/KG*: **60**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GP202

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **60**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2X50 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GP202-H

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **60**

Net weight: **6**

Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2X50 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	49
Water absorption capacity L/KG*:	27
Net weight:	2.7
Qty / pallet:	48

ARTICLE CODE

GP203

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

GP203-B


 Oil absorption
 capacity L/KG*: **49**

 Water absorption
 capacity L/KG*: **27**

 Net weight: **2.7**

 Qty / pallet: **48**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GP211-D

Oil absorption capacity L/KG*:	90
Water absorption capacity L/KG*:	50
Net weight:	6.24
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GP211-H

Oil absorption capacity L/KG*:	85
Water absorption capacity L/KG*:	58
Net weight:	6.4
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GP218-D

Oil absorption capacity L/KG*:	72
Water absorption capacity L/KG*:	40
Net weight:	4.992
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8X10 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GP218-H

Oil absorption capacity L/KG*:	68
Water absorption capacity L/KG*:	47
Net weight:	5.12
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8X10 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GP221-D

Oil absorption capacity L/KG*:	88
Water absorption capacity L/KG*:	60
Net weight:	6.64
Qty / pallet:	24

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GP221-D-S

Oil absorption capacity L/KG*:	88
Water absorption capacity L/KG*:	60
Net weight:	6.64
Qty / pallet:	24

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GP221-H

Oil absorption capacity L/KG*:	80
Water absorption capacity L/KG*:	60
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **166**

Water absorption
capacity L/KG*: **87**

Net weight: **8.64**

Qty / pallet: **15**

ARTICLE CODE

GR101

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **111**

Water absorption
capacity L/KG*: **58**

Net weight: **5.76**

Qty / pallet: **15**

ARTICLE CODE

GR101-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR101-H

Oil absorption
capacity L/KG*: **156**

Water absorption
capacity L/KG*: **87**

Net weight: **8.64**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR102

 Oil absorption
 capacity L/KG*: **166**

 Water absorption
 capacity L/KG*: **87**

 Net weight: **8.64**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC

Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	83
Water absorption capacity L/KG*:	44
Net weight:	4.32
Qty / pallet:	24

ARTICLE CODE

GR102-1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X60M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR102-B

 Oil absorption
 capacity L/KG*: **111**

 Water absorption
 capacity L/KG*: **58**

 Net weight: **5.76**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR102-H

Oil absorption
capacity L/KG*: **156**

Water absorption
capacity L/KG*: **87**

Net weight: **8.64**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR109-D

 Oil absorption
 capacity L/KG*: **1798**

 Water absorption
 capacity L/KG*: **1037**

 Net weight: **115.2**

 Qty / pallet: **1**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

1 Mat 1.60X400M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR111-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	83
Net weight:	9.216
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M length perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR112-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	83
Net weight:	9.216
Qty / pallet:	12

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR129

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR129L

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

GR201

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

GR201-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR201-H

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR201-H-NP

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR202

 Oil absorption
 capacity L/KG*: **173**

 Water absorption
 capacity L/KG*: **96**

 Net weight: **9.6**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **48**

Net weight: **4.8**

Qty / pallet: **15**

ARTICLE CODE

GR202-1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR202-B

 Oil absorption
 capacity L/KG*: **173**

 Water absorption
 capacity L/KG*: **96**

 Net weight: **9.6**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR202-D

 Oil absorption
 capacity L/KG*: **173**

 Water absorption
 capacity L/KG*: **96**

 Net weight: **9.6**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR202-H

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **96**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR202-H1

Oil absorption capacity L/KG*:	70
Water absorption capacity L/KG*:	48
Net weight:	4.8
Qty / pallet:	24

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR211-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	80
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR211-H

Oil absorption capacity L/KG*:	136
Water absorption capacity L/KG*:	93
Net weight:	10.24
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR212-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	80
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR212-H

Oil absorption capacity L/KG*:	136
Water absorption capacity L/KG*:	93
Net weight:	10.24
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR212-H1

Oil absorption capacity L/KG*:	68
Water absorption capacity L/KG*:	47
Net weight:	5.12
Qty / pallet:	24

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR220-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR221-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR221-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR222-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR222-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	96
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR223-D

Oil absorption capacity L/KG*:	44
Water absorption capacity L/KG*:	30
Net weight:	3.32
Qty / pallet:	36

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

GR223-H

Oil absorption capacity L/KG*:	40
Water absorption capacity L/KG*:	30
Net weight:	3.32
Qty / pallet:	36

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR224-D

Oil absorption capacity L/KG*:	27
Water absorption capacity L/KG*:	18
Net weight:	1.992
Qty / pallet:	56

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
FOLDED ROLLS	To be use as a roll, a sock, a pad according to the spill.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR224-D-S

Oil absorption capacity L/KG*:	27
Water absorption capacity L/KG*:	18
Net weight:	1.992
Qty / pallet:	56

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
FOLDED ROLLS	To be use as a roll, a sock, a pad according to the spill.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GR224-H

Oil absorption capacity L/KG*:	24
Water absorption capacity L/KG*:	18
Net weight:	1.992
Qty / pallet:	56

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
FOLDED ROLLS	To be use as a roll, a sock, a pad according to the spill.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GS1

 Oil absorption
 capacity L/KG*: **125**

 Water absorption
 capacity L/KG*: **72**

 Net weight: **8**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Socks 7.5CMX1.20M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	To absorb and clean small quantity
SOCKS	Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

GS2

 Oil absorption
 capacity L/KG*: **125**

 Water absorption
 capacity L/KG*: **72**

 Net weight: **8**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8 Socks 7.5CMX3M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	To absorb and clean small quantity
SOCKS	Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

GS3



Oil absorption capacity L/KG*:	89
Water absorption capacity L/KG*:	51
Net weight:	5.66
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Sock 7.5CMX18M

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	To absorb and clean small quantity
SOCKS	Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.
FLOCKS	Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

K103

Oil absorption capacity L/KG*: **88**Water absorption capacity L/KG*: **0**Net weight: **5.6**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 5 Pillows Ø.20CMX0.80M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SPILL CUSHIONS

Absorb large volumes of liquid quickly or use to "dam" a spill. Example: Once a spill has been contained with booms, cushions will absorb large amounts quickly.

PURE FIBRE

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

M0360056

Oil absorption capacity L/KG*:	28
Water absorption capacity L/KG*:	16
Net weight:	1.92
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.56CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

M180P

Oil absorption capacity L/KG*:	62
Water absorption capacity L/KG*:	37
Net weight:	3.6864
Qty / pallet:	24

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 32X32CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

OF-90075

Oil absorption capacity L/KG*:	64
Water absorption capacity L/KG*:	48
Net weight:	5.312
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

OF-9075

Oil absorption capacity L/KG*:	64
Water absorption capacity L/KG*:	48
Net weight:	5.312
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

SFG2202

Oil absorption capacity L/KG*:	11
Water absorption capacity L/KG*:	6
Net weight:	0.71
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.34CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **0**

Water absorption
capacity L/KG*: **0**

Net weight: **25**

Qty / pallet: **2**

ARTICLE CODE

SH06

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 kg Pure fiber

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	234
Water absorption capacity L/KG*:	0
Net weight:	13.44
Qty / pallet:	8

ARTICLE CODE

SH150

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.96X40M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

SOLM0360056

Oil absorption capacity L/KG*:	28
Water absorption capacity L/KG*:	16
Net weight:	1.92
Qty / pallet:	60

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

25 Drum top pads Ø.56CM

APPLICATION

GREY HYDROPHILIC	Absorbs most industrial liquids (hydrocarbons and derivative products, cutting oil, hydraulic fluids, coolants, mineral oil, solvents, water, etc...).
	Products are reinforced on one side to give the product durability.
DRUM TOP PAD	For minor leaks or spills on land or water. Example: minor leaks at a fuel delivery point.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **185**

Water absorption
capacity L/KG*: **0**

Net weight: **7**

Qty / pallet: **10**

ARTICLE CODE

WB110B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

1 Boom Ø13CMX10M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **740**

Water absorption
capacity L/KG*: **0**

Net weight: **28**

Qty / pallet: **2**

ARTICLE CODE

WB11B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 40 Booms Ø13CMX1M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **462**

Water absorption capacity L/KG*: **0**

Net weight: **17.5**

Qty / pallet: **4**

ARTICLE CODE

WB125B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Boom Ø13CMX25M 1M OUT ROPE

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WB13

 Oil absorption
 capacity L/KG*: **222**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8.4**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø13X3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **222**

Water absorption capacity L/KG*: **0**

Net weight: **8.4**

Qty / pallet: **12**

ARTICLE CODE

WB13B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø13CMX3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	359
Water absorption capacity L/KG*:	0
Net weight:	13.58
Qty / pallet:	10

ARTICLE CODE

WB15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø13X5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **185**

Water absorption capacity L/KG*: **0**

Net weight: **7**

Qty / pallet: **10**

ARTICLE CODE

WB15B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø13CMX5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **291**

Water absorption capacity L/KG*: **0**

Net weight: **11**

Qty / pallet: **6**

ARTICLE CODE

WB210B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Boom Ø20X10M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **726**

Water absorption capacity L/KG*: **0**

Net weight: **27.5**

Qty / pallet: **2**

ARTICLE CODE

WB212B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 2 Booms Ø20X12.5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **726**

Water absorption
capacity L/KG*: **0**

Net weight: **27.5**

Qty / pallet: **2**

ARTICLE CODE

WB225

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 1 Boom Ø20X25M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **726**

Water absorption
capacity L/KG*: **0**

Net weight: **27.5**

Qty / pallet: **2**

ARTICLE CODE

WB225B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 1 Boom Ø20X25M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WB23

Oil absorption capacity L/KG*:	349
Water absorption capacity L/KG*:	0
Net weight:	13.2
Qty / pallet:	5

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø20X3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	349
Water absorption capacity L/KG*:	0
Net weight:	13.2
Qty / pallet:	5

ARTICLE CODE

WB23B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø20X3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	349
Water absorption capacity L/KG*:	0
Net weight:	13.2
Qty / pallet:	5

ARTICLE CODE

WB23B-S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø20X3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **396**

Water absorption capacity L/KG*: **0**

Net weight: **15**

Qty / pallet: **6**

ARTICLE CODE

WB25

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø20X5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **291**

Water absorption capacity L/KG*: **0**

Net weight: **11**

Qty / pallet: **6**

ARTICLE CODE

WB25B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø20X5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WB25B2

 Oil absorption
 capacity L/KG*: **291**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **11**

 Qty / pallet: **6**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø20X5M EN CARTON

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **436**

Water absorption capacity L/KG*: **0**

Net weight: **16.5**

Qty / pallet: **3**

ARTICLE CODE

WB25B-3

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 3 Booms Ø20X5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **291**

Water absorption capacity L/KG*: **0**

Net weight: **11**

Qty / pallet: **6**

ARTICLE CODE

WB25B-S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø20X5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WB26

Oil absorption capacity L/KG*:	349
Water absorption capacity L/KG*:	0
Net weight:	13.2
Qty / pallet:	5

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Booms Ø.20CM X 6M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WB43R

 Oil absorption
 capacity L/KG*: **222**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8.4**

 Qty / pallet: **5**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø20X3M reinforced

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WB43R-L

 Oil absorption
 capacity L/KG*: **222**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8.4**

 Qty / pallet: **5**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø20X3M reinforced

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WBE13-3

 Oil absorption
 capacity L/KG*: **222**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8.4**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø13X3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	349
Water absorption capacity L/KG*:	0
Net weight:	13.2
Qty / pallet:	5

ARTICLE CODE

WBE20-3

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Booms Ø20X3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
FIBER BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **317**

Water absorption capacity L/KG*: **0**

Net weight: **12**

Qty / pallet: **2**

ARTICLE CODE

WBJ10B1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 1 Boom Ø16X10M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **634**

Water absorption capacity L/KG*: **0**

Net weight: **24**

Qty / pallet: **2**

ARTICLE CODE

WBJ10B2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 2 Skirted Booms Ø16X10M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **381**

Water absorption capacity L/KG*: **0**

Net weight: **14.4**

Qty / pallet: **2**

ARTICLE CODE

WBJ12B1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 1 Boom Ø16X12M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **761**

Water absorption capacity L/KG*: **0**

Net weight: **28.8**

Qty / pallet: **2**

ARTICLE CODE

WBJ12B2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 2 Skirted Booms Ø16X12M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **792**

Water absorption capacity L/KG*: **0**

Net weight: **30**

Qty / pallet: **2**

ARTICLE CODE

WBJ25B1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 1 Boom Ø16X25M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **571**

Water absorption capacity L/KG*: **0**

Net weight: **21.6**

Qty / pallet: **3**

ARTICLE CODE

WBJ3B6

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 6 Booms Ø16X3M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **317**

Water absorption capacity L/KG*: **0**

Net weight: **12**

Qty / pallet: **2**

ARTICLE CODE

WBJ5B2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 2 Skirted Booms Ø16X5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **634**

Water absorption capacity L/KG*: **0**

Net weight: **24**

Qty / pallet: **2**

ARTICLE CODE

WBJ5B4

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Big Bag of 4 Skirted Booms Ø16X5M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Pure fiber maximum absorption
SKIRTED BOOMS	Use pro-actively at outfalls and to contain large spills on land or water (Rivers, harbours, ponds, lakes or dealing with oil spills on land when its raining). Example: A boom deployed pro-actively at an outfall will contain any spilt oils that have accessed the drain.
PURE FIBRE	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC1

 Oil absorption
 capacity L/KG*: **125**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 16 Cushions 40X40CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

CUSHIONS INDUSTRY

Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC2

 Oil absorption
 capacity L/KG*: **156**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **10**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4 Cushions 60X80CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

CUSHIONS INDUSTRY

Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC25

Oil absorption capacity L/KG*: **63**Water absorption capacity L/KG*: **0**Net weight: **4**Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 25 Cushions 25X25CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

CUSHIONS INDUSTRY

Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **172**

Water absorption
capacity L/KG*: **0**

Net weight: **11**

Qty / pallet: **12**

ARTICLE CODE

WC3

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10 Pillows 30X60CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

CUSHIONS INDUSTRY

Line drip trays, use when carrying out maintenance of valves or pipework or as part of your spill response plan.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **78**

Water absorption
capacity L/KG*: **0**

Net weight: **5**

Qty / pallet: **20**

ARTICLE CODE

WC4

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10 Pillows Ø.13X60CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SPILL CUSHIONS

Absorb large volumes of liquid quickly or use to "dam" a spill. Example: Once a spill has been contained with booms, cushions will absorb large amounts quickly.

PURE FIBRE

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC5

Oil absorption capacity L/KG*: **88**Water absorption capacity L/KG*: **0**Net weight: **5.6**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4 Pillows Ø.20CMX1M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SPILL CUSHIONS

Absorb large volumes of liquid quickly or use to "dam" a spill. Example: Once a spill has been contained with booms, cushions will absorb large amounts quickly.

PURE FIBRE

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **146**

Water absorption capacity L/KG*: **0**

Net weight: **5.5**

Qty / pallet: **12**

ARTICLE CODE

WC50

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 10 Pillows Ø.20CMX50CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SPILL CUSHIONS

Absorb large volumes of liquid quickly or use to "dam" a spill. Example: Once a spill has been contained with booms, cushions will absorb large amounts quickly.

PURE FIBRE

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC501

Oil absorption capacity L/KG*:	40
Water absorption capacity L/KG*:	0
Net weight:	2.28
Qty / pallet:	42

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Pads 30X40CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
ULTRA HEAVY WEIGHT	Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC502

Oil absorption capacity L/KG*: **67**Water absorption capacity L/KG*: **0**Net weight: **3.8**Qty / pallet: **30**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 10 Pads 50X80CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC503

Oil absorption capacity L/KG*:	30
Water absorption capacity L/KG*:	0
Net weight:	1.71
Qty / pallet:	48

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 20 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
ULTRA HEAVY WEIGHT	Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WC6

Oil absorption capacity L/KG*: **88**Water absorption capacity L/KG*: **0**Net weight: **5.6**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 24 Cushions 28X35CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SPILL CUSHIONS

Absorb large volumes of liquid quickly or use to "dam" a spill. Example: Once a spill has been contained with booms, cushions will absorb large amounts quickly.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WCMPD

Oil absorption capacity L/KG*:	0
Water absorption capacity L/KG*:	0
Net weight:	0.5
Qty / pallet:	12

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

1 pillow white ho Ø.20CMX45CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	To absorb and clean small quantity
SPILL CUSHIONS	Absorb large volumes of liquid quickly or use to "dam" a spill. Example: Once a spill has been contained with booms, cushions will absorb large amounts quickly.
NC	

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

WDP101

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 40X50CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WDP201


 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 40X50CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WDP201C

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WDP201-S

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 40X50CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **54**

Water absorption
capacity L/KG*: **0**

Net weight: **3**

Qty / pallet: **20**

ARTICLE CODE

WDP202/2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 50 Pads 40X50CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **24**

ARTICLE CODE

WDP301

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 40 Pads 0.80X1M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	166
Water absorption capacity L/KG*:	0
Net weight:	8.64
Qty / pallet:	15

ARTICLE CODE

WDR101

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X60M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **166**

Water absorption capacity L/KG*: **0**

Net weight: **8.64**

Qty / pallet: **15**

ARTICLE CODE

WDR102

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X60M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

WDR201

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X40M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **216**

Water absorption
capacity L/KG*: **0**

Net weight: **12**

Qty / pallet: **12**

ARTICLE CODE

WDR201SP1M

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 1X40M SP

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

WDR202

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X40M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **0**

Net weight: **4.8**

Qty / pallet: **30**

ARTICLE CODE

WDR202/2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.40X40M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WM101-D

Oil absorption capacity L/KG*:	96
Water absorption capacity L/KG*:	0
Net weight:	7.2
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X40M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottomlayer that acts as a barrier protecting the surface its used on making them ideal for use in areas where constant drips or overspray would otherwise contaminate the surface.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM101-H

Oil absorption
capacity L/KG*: **96**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X40M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottomlayer that acts as a barrier protecting the surface its used on making them ideal for use in areas where constant drips or overspray would otherwise contaminate the surface.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM104-H

Oil absorption
capacity L/KG*: **191**

Water absorption
capacity L/KG*: **0**

Net weight: **14.4**

Qty / pallet: **6**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.60X40M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottomlayer that acts as a barrier protecting the surface its used on making them ideal for use in areas where constant drips or overspray would otherwise contaminate the surface.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE


WM310-D

Oil absorption capacity L/KG*:	39
Water absorption capacity L/KG*:	0
Net weight:	4.63
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 50 Mats 40X50CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM310-H



Oil absorption capacity L/KG*:	39
Water absorption capacity L/KG*:	0
Net weight:	4.63
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 50 Mats 40X50CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM310-H-S




Oil absorption capacity L/KG*:	39
Water absorption capacity L/KG*:	0
Net weight:	4.63
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 50 Mats 40X50CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE


WM311-D

Oil absorption capacity L/KG*:	94
Water absorption capacity L/KG*:	0
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Mats 0.40X30M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM311-H

Oil absorption capacity L/KG*:	94
Water absorption capacity L/KG*:	0
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Mats 0.40X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM311-H-S

Oil absorption capacity L/KG*:	94
Water absorption capacity L/KG*:	0
Net weight:	11.112
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Mats 0.40X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


WM312-D

Oil absorption capacity L/KG*:	94
Water absorption capacity L/KG*:	0
Net weight:	11.112
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X30M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM312-H

Oil absorption capacity L/KG*:	94
Water absorption capacity L/KG*:	0
Net weight:	11.112
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM312-H-S

Oil absorption capacity L/KG*:	94
Water absorption capacity L/KG*:	0
Net weight:	11.112
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


WM313-D

Oil absorption capacity L/KG*:	140
Water absorption capacity L/KG*:	0
Net weight:	16.668
Qty / pallet:	8

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.20X30M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM313-H

Oil absorption capacity L/KG*:	140
Water absorption capacity L/KG*:	0
Net weight:	16.668
Qty / pallet:	8


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.20X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE


WM314-D

Oil absorption capacity L/KG*:	187
Water absorption capacity L/KG*:	0
Net weight:	22.224
Qty / pallet:	6

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.60X30M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
MATS	Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT:	No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
SECURITY:	No specific risk. For further information, please refer to the material safety data sheet.
STORAGE:	Store in a dry and cool place.
DISPOSABILITY:	The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM314-H

Oil absorption capacity L/KG*:	187
Water absorption capacity L/KG*:	0
Net weight:	22.224
Qty / pallet:	6


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.60X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM315

Oil absorption capacity L/KG*:	142
Water absorption capacity L/KG*:	0
Net weight:	16.7915
Qty / pallet:	6


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.42X25M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM315-H

Oil absorption capacity L/KG*:	197
Water absorption capacity L/KG*:	0
Net weight:	20.52
Qty / pallet:	8


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.42X25M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

RAILMAT

The mat allows rain water to run off, but traps oil based spills. It can be use outdoor thanks to its strong layer UV stabilised. It is very effective for preventing oil and petroleum based fluids leaking from rail vehicles onto the ballast. The base layer is impermeable and prevents spills from reaching the surface below.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WM316-D

Oil absorption capacity L/KG*:	38
Water absorption capacity L/KG*:	0
Net weight:	4.4448
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Mats 80X60CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


WM316-H

Oil absorption capacity L/KG*:	38
Water absorption capacity L/KG*:	0
Net weight:	4.4448
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Mats 80X60CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM326-H

Oil absorption capacity L/KG*:	2
Water absorption capacity L/KG*:	0
Net weight:	0.22224
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

1 Mat 80X60CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WM328-D



Oil absorption capacity L/KG*:	690
Water absorption capacity L/KG*:	0
Net weight:	82.08
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Mats 80X200CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM398-H

Oil absorption capacity L/KG*:	6
Water absorption capacity L/KG*:	0
Net weight:	0.6482
Qty / pallet:	0

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

1 Mat 1.40X1M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM399-H

Oil absorption capacity L/KG*:	78
Water absorption capacity L/KG*:	0
Net weight:	9.26
Qty / pallet:	8


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.00X20M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM413-H

Oil absorption capacity L/KG*:	99
Water absorption capacity L/KG*:	0
Net weight:	10.2875
Qty / pallet:	18


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 0.50X25M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WM415-H

Oil absorption capacity L/KG*:	281
Water absorption capacity L/KG*:	0
Net weight:	29.2165
Qty / pallet:	6


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.42X25M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


WMO320-H

Oil absorption capacity L/KG*:	39
Water absorption capacity L/KG*:	0
Net weight:	4.63
Qty / pallet:	30

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 50 Mats 40X50CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WMO321-H

Oil absorption capacity L/KG*:	98
Water absorption capacity L/KG*:	0
Net weight:	11.592
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Mats 0.40X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WMO322-H

Oil absorption capacity L/KG*:	98
Water absorption capacity L/KG*:	0
Net weight:	11.592
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Mat 0.80X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WMO323-H

Oil absorption capacity L/KG*:	146
Water absorption capacity L/KG*:	0
Net weight:	17.388
Qty / pallet:	8


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.20X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WMO324-H

Oil absorption capacity L/KG*:	195
Water absorption capacity L/KG*:	0
Net weight:	23.184
Qty / pallet:	6


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Mat 1.60X30M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


WMO326-H

Oil absorption capacity L/KG*:	2
Water absorption capacity L/KG*:	0
Net weight:	0.23184
Qty / pallet:	0

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

1 Mat 80X60CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE


WMO327-H

Oil absorption capacity L/KG*:	39
Water absorption capacity L/KG*:	0
Net weight:	4.6368
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Mats 80X60CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WMO328-H

Oil absorption capacity L/KG*:	38
Water absorption capacity L/KG*:	0
Net weight:	4.4448
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10 Mats 80X120CM

APPLICATION

**WHITE
HYDROPHOBIC**

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WMO329-H

Oil absorption capacity L/KG*:	65
Water absorption capacity L/KG*:	0
Net weight:	7.73
Qty / pallet:	15


*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10 Mats 80X200CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products have a non-porous bottom layer and also have a reinforced top surface making them ideal for areas of high foot traffic or even fork lift truck movement.

MATS

Catch overspray, reduce slip hazards and stop liquid being tracked from one area to another.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **139**

Water absorption capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

WP101

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **139**

Water absorption capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

WP101-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP101-H

Oil absorption
capacity L/KG*: **130**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **139**

Water absorption capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

WP101-S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **139**

Water absorption capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

WP102

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **20**

ARTICLE CODE

WP102-20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10X20 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP102-H

Oil absorption
capacity L/KG*: **130**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4X50 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	63
Water absorption capacity L/KG*:	0
Net weight:	3.24
Qty / pallet:	24

ARTICLE CODE

WP103

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WP103/2

Oil absorption capacity L/KG*:	32
Water absorption capacity L/KG*:	0
Net weight:	1.62
Qty / pallet:	48

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	63
Water absorption capacity L/KG*:	0
Net weight:	3.24
Qty / pallet:	24

ARTICLE CODE

WP103/4

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 4x50 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	63
Water absorption capacity L/KG*:	0
Net weight:	3.24
Qty / pallet:	24

ARTICLE CODE

WP103-S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 200 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WP111-D

Oil absorption capacity L/KG*: **120**Water absorption capacity L/KG*: **0**Net weight: **7.68**Qty / pallet: **16**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 200 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced on one side to give the product durability.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **0**

Net weight: **7.2**

Qty / pallet: **16**

ARTICLE CODE

WP120

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 10X20 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WP201

Oil absorption capacity L/KG*: **108**Water absorption capacity L/KG*: **0**Net weight: **6**Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.


STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **0**

Net weight: **6**

Qty / pallet: **20**

ARTICLE CODE

WP201A

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WP201-B

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP201-H

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **0**

Net weight: **6**

Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WP201-S


 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WP202

 Oil absorption
 capacity L/KG*: **108**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2X50 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP202-H

Oil absorption
capacity L/KG*: **87**

Water absorption
capacity L/KG*: **0**

Net weight: **6**

Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2X50 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WP203


 Oil absorption
 capacity L/KG*: **49**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **2.7**

 Qty / pallet: **48**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WP203-B

Oil absorption capacity L/KG*: **54**Water absorption capacity L/KG*: **0**Net weight: **3**Qty / pallet: **48**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 100 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WP211-D

Oil absorption capacity L/KG*:	90
Water absorption capacity L/KG*:	0
Net weight:	6.24
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP211-H

Oil absorption capacity L/KG*:	85
Water absorption capacity L/KG*:	0
Net weight:	6.4
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced on one side to give the product durability.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP211-H-S

Oil absorption capacity L/KG*:	85
Water absorption capacity L/KG*:	0
Net weight:	6.4
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced on one side to give the product durability.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP213-H

Oil absorption capacity L/KG*:	39
Water absorption capacity L/KG*:	0
Net weight:	2.88
Qty / pallet:	48

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced on one side to give the product durability.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WP221-D

Oil absorption capacity L/KG*:	88
Water absorption capacity L/KG*:	0
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP221-H

Oil absorption capacity L/KG*:	80
Water absorption capacity L/KG*:	0
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WP221-H-S

Oil absorption capacity L/KG*:	80
Water absorption capacity L/KG*:	0
Net weight:	6.64
Qty / pallet:	20

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 40X50CM length perforated 20 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WP223-D

Oil absorption capacity L/KG*:	40
Water absorption capacity L/KG*:	0
Net weight:	2.988
Qty / pallet:	48

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 30X30CM

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
PADS INDUSTRY	For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WP950G

Oil absorption capacity L/KG*:	877
Water absorption capacity L/KG*:	0
Net weight:	50.35
Qty / pallet:	2

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 100 Pads 53X100CM

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

PADS INDUSTRY

For minor leaks and spills in the workplace, on land or water. Example: minor leaks at a fuel delivery poing.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WR101

 Oil absorption
 capacity L/KG*: **166**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8.64**

 Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **111**

Water absorption capacity L/KG*: **0**

Net weight: **5.76**

Qty / pallet: **15**

ARTICLE CODE

WR101-40

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **111**

Water absorption
capacity L/KG*: **0**

Net weight: **5.76**

Qty / pallet: **20**

ARTICLE CODE

WR101-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

LIGHT WEIGHT

Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR101-H

Oil absorption
capacity L/KG*: **156**

Water absorption
capacity L/KG*: **0**

Net weight: **8.64**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **166**

Water absorption capacity L/KG*: **0**

Net weight: **8.64**

Qty / pallet: **15**

ARTICLE CODE

WR102

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	83
Water absorption capacity L/KG*:	0
Net weight:	4.32
Qty / pallet:	15

ARTICLE CODE

WR102-1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X60M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR102-H

Oil absorption capacity L/KG*:	156
Water absorption capacity L/KG*:	0
Net weight:	8.64
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X60M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WR111-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	0
Net weight:	9.216
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X60M lenght perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WR112-D

Oil absorption capacity L/KG*:	96
Water absorption capacity L/KG*:	0
Net weight:	6.144
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
LIGHT WEIGHT	Standard absorption capacity for prevention of drip-dryings

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

WR201

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **173**

Water absorption capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

WR201-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR201-H

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **173**

Water absorption capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

WR202

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **87**

Water absorption capacity L/KG*: **0**

Net weight: **4.8**

Qty / pallet: **15**

ARTICLE CODE

WR202-1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **173**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

ARTICLE CODE

WR202-B

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR202-H

Oil absorption
capacity L/KG*: **139**

Water absorption
capacity L/KG*: **0**

Net weight: **9.6**

Qty / pallet: **15**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR202-H1

Oil absorption capacity L/KG*:	70
Water absorption capacity L/KG*:	0
Net weight:	4.8
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **87**

Water absorption capacity L/KG*: **0**

Net weight: **4.8**

Qty / pallet: **15**

ARTICLE CODE

WR202S

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WR211-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	0
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR211-H

Oil absorption capacity L/KG*:	136
Water absorption capacity L/KG*:	0
Net weight:	10.24
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WR212-D

Oil absorption capacity L/KG*:	144
Water absorption capacity L/KG*:	0
Net weight:	9.984
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced on one side to give the product durability.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR212-H

Oil absorption capacity L/KG*:	136
Water absorption capacity L/KG*:	0
Net weight:	10.24
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced on one side to give the product durability.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR212-H1

Oil absorption capacity L/KG*:	68
Water absorption capacity L/KG*:	0
Net weight:	5.12
Qty / pallet:	24

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced on one side to give the product durability.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WR221-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M lenght perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR221-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR221-H-S

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.80X40M length perforated 40 cm and cross 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WR222-D

Oil absorption capacity L/KG*:	141
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR222-H

Oil absorption capacity L/KG*:	128
Water absorption capacity L/KG*:	0
Net weight:	10.624
Qty / pallet:	15

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Rolls 0.40X40M cross perforated 50 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

- TRANSPORT:** No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.
- SECURITY:** No specific risk. For further information, please refer to the material safety data sheet.
- STORAGE:** Store in a dry and cool place.
- DISPOSABILITY:** The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WR224-D

Oil absorption capacity L/KG*:	27
Water absorption capacity L/KG*:	0
Net weight:	1.992
Qty / pallet:	56

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

HexaDyn®

ARTICLE CODE

WR224-H

Oil absorption capacity L/KG*:	24
Water absorption capacity L/KG*:	0
Net weight:	1.992
Qty / pallet:	56

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Roll 0.40X15M cross perforated 50 cm 3 timesto

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



Products are reinforced and 100% lint free on both sides, which means they are hard wearing and durable and makes them ideal for applications where you can't afford any cross contamination.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

HEAVY WEIGHT

Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*:	234
Water absorption capacity L/KG*:	0
Net weight:	13.44
Qty / pallet:	8

ARTICLE CODE

WR301

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.96X40M cross perforated 48 cm

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.
ROLLS	Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WR501

 Oil absorption
 capacity L/KG*: **199**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **11.4**

 Qty / pallet: **9**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.80X15M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption capacity L/KG*: **199**

Water absorption capacity L/KG*: **0**

Net weight: **11.4**

Qty / pallet: **9**

ARTICLE CODE

WR502

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 2 Rolls 0.40X15M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

Oil absorption
capacity L/KG*: **100**

Water absorption
capacity L/KG*: **0**

Net weight: **5.7**

Qty / pallet: **9**

ARTICLE CODE

WR502-1

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Bag of 1 Roll 0.40X15M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



For the highest absorption speed and capacity when dealing with liquids on the ground or the surface of water. The absorbed amount is proportional to the thickness of the product. Products for spill response are not perforated. For pro-active industrial applications pads and rolls are perforated to save you money.

ROLLS

Fast to deploy and cover large areas quickly. Example: can be "streamed out" behind a boat on calm water to cover a large area quickly.

ULTRA HEAVY WEIGHT

Maximum absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WS1

 Oil absorption
 capacity L/KG*: **125**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 20 Socks 7.5CMX1.20M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SOCKS

Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WS2

Oil absorption capacity L/KG*: **125**Water absorption capacity L/KG*: **0**Net weight: **8**Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 8 Socks 7.5CMX3M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SOCKS

Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WS3

 Oil absorption
 capacity L/KG*: **94**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **6**

 Qty / pallet: **20**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 1 Sock 7.5CMX18M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SOCKS

Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET



PURE POLYPROPYLENE SORBENT

ARTICLE CODE

WS6

 Oil absorption
 capacity L/KG*: **125**

 Water absorption
 capacity L/KG*: **0**

 Net weight: **8**

 Qty / pallet: **12**

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4 Socks 7.5CMX6M

APPLICATION

WHITE HYDROPHOBIC

Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.



To absorb and clean small quantity

SOCKS

Contain liquids at the base of leakymachinery and stop it spreading into other areas or use to contain spilt liquids.

FLOCKS

Standard absorption capacity.

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WZ1-D

Oil absorption capacity L/KG*:	143
Water absorption capacity L/KG*:	0
Net weight:	9.9216
Qty / pallet:	10

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4 Sweeps 0.48X15M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
SWEEPS	Use with oil selective booms when dealing with hydrocarbon spill on water.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WZ2-D

Oil absorption capacity L/KG*:	143
Water absorption capacity L/KG*:	0
Net weight:	9.9216
Qty / pallet:	10

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Sweeps 0.48X30M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
SWEEPS	Use with oil selective booms when dealing with hydrocarbon spill on water.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WZ3-D

Oil absorption capacity L/KG*:	143
Water absorption capacity L/KG*:	0
Net weight:	9.9216
Qty / pallet:	10

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 4 Sweeps 0.48X15M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
SWEEPS	Use with oil selective booms when dealing with hydrocarbon spill on water.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TECHNICAL DATA SHEET

PURE POLYPROPYLENE SORBENT



ARTICLE CODE

WZ4-D

Oil absorption capacity L/KG*:	143
Water absorption capacity L/KG*:	0
Net weight:	9.9216
Qty / pallet:	10

*The absorption capacity is calculated in accordance with the EDANA norm : putting of a sample in a 20W50 oil bath at 25°C until saturation and weighing after a 2 min. vertical draining.

Box of 2 Sweeps 0.48X30M

APPLICATION

WHITE HYDROPHOBIC	Absorbs industrial hydrocarbons and derivative products (petrol, oil, diesel oil, benzene, mineral oil, etc...) but not water-based liquids. Do not use on soapy water the absorbent would dive.
	Products are reinforced on one side to give the product durability.
SWEEPS	Use with oil selective booms when dealing with hydrocarbon spill on water.
HEAVY WEIGHT	Superior absorption capacity for pollutions treatment

WHY USE POLYPROPYLENE ABSORBENTS?

Polypropylene absorbents provide:

- Exceptional absorbency (up to 25 times their own weight)
- Selective absorption : 3 types available (Oil Selective - General Purpose - Chemical) allowing you to absorb almost any liquid.

The use and disposal of Polypropylene absorbents saves you time and money:

- Quick and easy to deploy, saving you time
- No dust or mesh to clean-up, saving you time
- They ensure the floor is slip free when used pro-actively, saving you money
- Unlike granules its easy to see how much you are using, saving you money
- Where legislation allows controlled incineration produces energy and reduces landfill (Ash content is a little as 0.05%) saving you money.

ADDITIONAL INFORMATION

TRANSPORT: No specific regulation, can stand extreme cold, to be kept away from heat > 160°C.

SECURITY: No specific risk. For further information, please refer to the material safety data sheet.

STORAGE: Store in a dry and cool place.

DISPOSABILITY: The absorbents must be disposed of in compliance with the absorbed chemical destruction regulation.

SPECIAL REMARKS

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must take independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.